

product datasheet

reverse thread drywall screw



www.evolutionfasteners.co.uk



Designed for:	Fixing low and medium density boards to drywall track and timber base materials.
Head Style:	Countersunk
Drive Bit:	Phillips 2
Coating:	Electroplated zinc
Shank Material:	Carbon steel
Threadform:	Single
Drill Point:	Super sharp point
Material Grade:	AISI C1022
Effective Thread Length:	Fully threaded

Evolution Fasteners (UK) Ltd
 Unit 2A & 2B
 Clyde Gateway Trade Park
 Dalmarnock Road
 Rutherglen
 Glasgow
 G73 1AE
 Tel: +44 (0)141 647 7100
 Fax: +44 (0)141 647 5100
 technical@evolutionfasteners.co.uk

Reverse Thread Drywall Screw Range					
Product Code	Size	Box Qty	Carton Qty	Steel Thickness	Drill Speed
DWRT32	3.9 x 32mm	1,000	10,000	0.5mm - 1.5mm	4,000 - 6,000 RPM
DWRT42	3.9 x 42mm	1,000	10,000	0.5mm - 1.5mm	4,000 - 6,000 RPM

Application Guide

Evolution reverse thread drywall screws should be used in medium density boards e.g. Knauf Tough Panel, Knauf Aqua Panel, British Gypsum Duraline and British Gypsum Sound Bloc.

These screws are used when a smoother finish is required.

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets