

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1



Replaces version from 16.05.10

Print Date:- 11.07.2017

## SECTION 1: Identification of the substance / mixture and of the company / undertaking.

### 1.1. Product identifier

Commercial Product Name (s) fischer FireStop Hand Foam

Product Part number (s) 42757

### 1.2. Relevant identified uses of the substance or mixture & uses advised against

Relevant identified uses Linear joint sealant for sealing gaps in walls, ceilings, floors, window / door joints, sills and frames.

Recommended restrictions No uses advised against known

### 1.3. Details of supplier of the safety data sheet

Name of Supplier: fischer fixings (UK) Ltd

Address of Supplier: Whitely Road,  
Wallingford,  
Oxfordshire,  
OX10 9AT

Telephone:- 01491 827920

Fax: 01491 827950

Responsible Person: Mrs Mirka Valovicova MSc (Hons)  
Technical Manager

E-mail: [Technical@fischer.co.uk](mailto:Technical@fischer.co.uk)

### 1.4. Emergency telephone number

Emergency Telephone number 01491 827 920 (office hours only)

## SECTION 2: Hazard identification

### 2.1 Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) 1272/2008

Class	Category	Hazard statement
Aerosol	Category 1	H222, Extremely flammable aerosol
Aerosol	Category 1	H229: Pressurized container: May burst if heated
Carc.	Category 2	H351: Suspected of causing cancer
Acute Tox.	Category 4	H332: Harmful if inhaled
STOT RE	Category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled
Eye Irrit.	Category 2	H319: Causes serious eye irritation
STOT SE	Category 3	H335: May cause respiratory irritation
Skin Irrit.	Category 2	H315: Causes skin irritation
Resp. Sens.	Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
Skin Sens.	Category 1	H317: May cause an allergic skin reaction

**Safety Data Sheet as per regulation (EC) 1907/2006**

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP]



GHS02



GHS07



GHS08

Signal word

Danger

Contains;-

polymethylene polyphenyl isocyanate

Hazard Statements

H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P405: Store locked up

P410 + P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

P501: Dispose of contents / container in accordance with local / national / international regulation.

Further Information

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask or appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**2.3 Other hazards**

Gas / Vapour spreads at floor level: ignition hazard

Contains component (s) included in the fluorinated greenhouse gases (Regulation (EU) No 517/2014).

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1



Replaces version from 16.05.10

Print Date:- 11.07.2017

## SECTION 3: Composition / information on ingredients.

**3.1 Substances** Not applicable

### 3.2. Mixtures

Name REACH Registration No.	CAS No. EC No.	Conc. C	Classification according to CLP	Note	Remark
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	1%<C<10%	Flam. gas 1; H220 Press. Gas-Liquefied gas; H280	(1)(2)(10)	Propellant
1,1-difluoroethane 01-2119474440-43	75-37-6 200-866-1	1%<C<10%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(10)	Propellant
polymethylene polyphenyl isocyanate	9016-87-9	C>25%	Carc.2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens.1; H334 Skin Sens. 1; H317	(1)(2)(8) (10)	Constituent
Isobutane 01-2119485395-27	75-28-5 200-857-2	1%<C<10%	Flam. gas 1; H220 Press. Gas-Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)					
reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester 01-2119486772-26		10%<C<25%	Acute Tox. 4; H302	1)(10)	Constituent
triethyl phosphate 01-2119492852-28	78-40-0 201-114-5	1%<C<10%	Acute Tox. 4; H302 Eye Irrit. 2; H319	(1)(10)	Constituent

- (1) For H-statements in full: see heading 16  
 (2) Substances with a community workplace exposure limit  
 (8) Specific concentration limits, see heading 16  
 (10) Subject to restrictions of Annex XVII of Regulation (EC) no. 1907/2006.

## SECTION 4: First aid measures.

### 4.1 Description of first aid measures

#### General advice:

#### Check the vital functions.

Unconscious: Maintain adequate airway and respiration.  
 Respiratory arrest: artificial respiration or oxygen.  
 Cardiac arrest: perform resuscitation.  
 Victim conscious with laboured breathing: half-seated.  
 Victim in shock: on their back with legs slightly raised.  
 Vomiting: prevent asphyxia /aspiration pneumonia.  
 Prevent cooling by covering the victim (no warming up).  
 Keep watching the victim. Give psychological aid.  
 Keep the victim calm, avoid physical strain.  
 Depending on the victim's condition: Contact doctor / hospital

#### After Inhalation:

Remove victim into fresh air.  
 Respiratory problems: consult a doctor / medical service.

#### After skin contact:

Wash immediately with lots of water.  
 Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse immediately with plenty of water.  
 Do not apply neutralising agents.  
 Take victim to an ophthalmologist if irritation persists

## Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**After ingestion:** Rinse mouth with water.  
Immediately after ingestion give lots of water to drink.  
DO NOT induce vomiting.  
Consult a doctor / medical service if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed.

#### 4.2.1 Acute symptoms

**After inhalation:** Dry / sore throat.  
Coughing.  
Irritation of the respiratory tract.  
Irritation of the nasal mucous membranes.  
Runny nose.

#### FOLLOWING SYMPTOMS MAY APPEAR LATER:

Possible inflammation of the respiratory tract.  
Risk of lung oedema.  
Respiratory difficulties.

**After skin contact:** Tingling / irritation of the skin.

**After eye contact:** Irritation of the eye tissue.  
Lacrimation.

**After Ingestion:** No effects known

**4.2.2 Delayed symptoms:** No effects known.

### 4.3 Indication of any immediate medical attention and special treatment needed.

If applicable and available it will be listed below

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**5.1.1 Suitable extinguishing media** BC powder. Carbon dioxide, Sand / earth

**5.1.2 Unsuitable extinguishing media** Solid water jet ineffective as extinguishing medium..

### 5.2 Special hazards arising from the substance or mixture.

Special hazards arising from the substance or mixture. On burning: release of toxic and corrosive gases / vapours (phosphorous oxides, nitrous vapours, hydrogen bromide, hydrofluoric acid, hydrogen chloride), (carbon monoxide-carbon dioxide).  
Pressurised container: May burst if heated.

### 5.3 Advice for firefighters

#### 5.3.1 Instructions

If exposed to fire, cool the closed containers by spraying with water  
Physical explosion risk: extinguish / cool from behind cover.  
Do not move the load if exposed to heat.  
After cooling: persistent risk of physical explosion.  
Dilute toxic gases with water spray.  
Take account of toxic / corrosive precipitation water.

#### 5.3.2 Special protective equipment for fire-fighters

Gloves.  
Protective goggles.  
Head/neck protection.  
Protective clothing  
Heat / fire exposure: compressed air / oxygen apparatus

## Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1



Replaces version from 16.05.10

Print Date:- 11.07.2017

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Stop engines and no smoking.  
No naked flames or sparks.  
Spark- and explosion proof appliances and lighting equipment

6.1.1 Protective equipment for non-emergency personnel. See heading 8.2

6.1.2 Protective equipment for emergency responders. Gloves.  
Protective goggles.  
Head/neck protection.  
Protective Clothing.  
Suitable protective clothing- See heading 8.2

#### 6.2 Environmental precautions.

Environmental precautions Dam up the liquid spill.  
Use appropriate containment to avoid environmental contamination.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up Allow products to solidify and remove it by mechanical means.  
Carefully collect the spill / leftovers.  
Clean (treat) contaminated surfaces with acetone.  
Take collected spill to manufacturer / competent authority.  
Wash clothing and equipment after handling.

6.4 Reference to other sections See sections 13

### SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1 Precautions for safe handling.

Advice on safe handling: Use spark-/ explosion proof appliances and lighting system.  
Keep away from naked flames / heat.  
Keep away from ignition sources / sparks.  
Gas / vapour heavier than air at 20°C  
Observe very strict hygiene- avoid contact.  
Remove contaminated clothing immediately.

#### 7.2 Conditions for safe storage, including any incompatibilities.

7.2.1 Safe storage requirements: Storage temperatures: < 50°C.  
Store in a cool dry area.  
Keep out of direct sunlight.  
Ventilation at floor level.  
Fireproof storeroom. Unauthorised persons not admitted.  
Meet the legal requirements.  
Max. storage time: 1 year (s).

7.2.2 Keep away from: Heat sources, ignition sources.

7.2.3 Suitable packaging material: Aerosol

7.2.4 Non-suitable packaging material: No data available

#### 7.3 Specific end use (s).

Specific use (s) If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**SECTION 8: Exposure controls / personal protection**

**8.1 Control parameters.**

**8.1.1 Occupational exposure**

a) Occupational exposure limit values If limit values are applicable and available these will be listed below.

<b>EU</b>		
Dimethylether	Time-weighted average exposure limit 8h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8h (Indicative occupational exposure limit value)	1920mg/m <sup>3</sup>
<b>Belgium</b>		
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C4)	Time-weighted average exposure limit 8h	1000 ppm
Oxyde de dimethyle	Time-weighted average exposure limit 8h	1000 ppm
	Time-weighted average exposure limit 8h	1920 mg/m <sup>3</sup>
<b>The Netherlands</b>		
Dimethylether	Time-weighted average exposure limit 8h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8h (Public occupational exposure limit value)	950 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m <sup>3</sup>
<b>France</b>		
Oxyde de dimethyle	Time-weighted average exposure limit 8h (VRI: Valeur reglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8h (VRI: Valeur reglementaire indicative)	1920mg/m <sup>2</sup>
<b>Germany</b>		
Dimethylether	Time-weighted average exposure limit 8h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8h (TRGS 900)	1900 mg/m <sup>3</sup>
Isobutan	Time-weighted average exposure limit 8h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8h (TRGS 900)	2400 mg/m <sup>3</sup>
pMDI (als MDI berechnet)	Time-weighted average exposure limit 8h (TRGS 900)	0.05 mg/m <sup>3</sup>
<b>UK</b>		
Dimethyl ether	Time-weighted average exposure limit 8h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8h (Workplace exposure limit (EH40/2005))	766 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m <sup>3</sup>
Isocyanates, all (as-NCO) Except methyl isocyanate	Time-weighted average exposure limit 8h (Workplace exposure limit (EH40/2005))	0.02mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	0.07 mg/m <sup>3</sup>
<b>USA (TLV-ACGIH)</b>		
Butane, all isomers	Short time value (TLV-Adopted Value)	1000 ppm

b) National biological limit values If limit values are applicable and available these will be listed below.

**8.1.2 Sampling methods**

If applicable and available it will be listed below.

<b>Sampling Methods</b>		
Isocyanates	NIOSH	5521
Isocyanates	NIOSH	5522

8.1.3 Applicable limit values when using the substance or mixture as intended. If limit values are applicable and available these will be listed below.

**8.1.4 DNEL/PNEC values**

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1



Replaces version from 16.05.10

Print Date:- 11.07.2017

## DNEL/DMEL- Workers

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester		
Effect level (DNEL/DMEL)	Type	Value
DNEL	Long-term systemic effects inhalation	5.82 mg/m <sup>3</sup>
	Acute systemic effects inhalation	22.4 mg/m <sup>3</sup>
	Long-term systemic effects dermal	2.08 mg/kg bw/day
	Acute systemic effects dermal	8mg/kg bw/day

triethyl phosphate		
Effect level (DNEL/DMEL)	Type	Value
DNEL	Long-term systemic effects inhalation	11.81 mg/m <sup>3</sup>
	Acute systemic effects inhalation	94.5 mg/m <sup>3</sup>
	Long-term systemic effects dermal	3.35 mg/kg bw/day
	Acute systemic effects dermal	26.8 mg/kg bw/day

## DNEL/DMEL- General Population

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester		
Effect level (DNEL/DMEL)	Type	Value
DNEL	Long-term systemic effects inhalation	1.46 mg/m <sup>3</sup>
	Acute systemic effects inhalation	11.2 mg/m <sup>3</sup>
	Long-term systemic effects dermal	1.04 mg/kg bw/day
	Acute systemic effects dermal	4 mg/kg bw/day
	Long-term systemic effects oral	0.52 mg/kg bw/day

triethyl phosphate		
Effect level (DNEL/DMEL)	Type	Value
DNEL	Long-term systemic effects inhalation	2.91 mg/m <sup>3</sup>
	Acute systemic effects inhalation	23.28 mg/m <sup>3</sup>
	Long-term systemic effects dermal	1.67 mg/kg bw/day
	Acute systemic effects dermal	13.36 mg/kg bw/day
	Long-term systemic effects oral	1.67 mg/kg bw/day
	Acute systemic effects oral	13.36 mg/kg bw/day

## PNEC

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester	
Compartments	Value
Fresh water	0.64 mg/l
Marine water	0.064 mg/l
Aqua (intermittent releases)	0.51 mg/l
STP	7.84 mg/l
Fresh water sediment	13.4 mg/kg sediment dw
Marine water sediment	1.34 mg/kg sediment dw
Soil	1.7 mg/kg soil dw
Oral	11.6 mg /kg food

triethyl phosphate		
Compartments	Value	Remark
Fresh water	0.632 mg/l	
Salt water	0.063 mg/l	
Aqua (intermittent releases)	9 mg/l	
STP	298.5 mg/l	

# Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

Fresh water sediment	5 mg/kg sediment dw	
Marine water sediment	0.5 mg/kg sediment dw	
Soil	0.64 mg/kg soil dw	

## 8.1.5 Control banding

If applicable and available it will be listed below.

## 8.2 Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Use spark / explosion proof appliances and lighting system.  
Keep away from ignition sources / sparks.  
Keep away from naked flames / heat  
Measure the concentration in the air regularly

### 8.2.2 Individual protection measures, such as personal protective equipment

General protective and hygiene measures

Observe very strict hygiene-avoid contact.  
Do not eat, drink or smoke during work

Respiratory protection

Wear gas mask with filter type A if conc. In air > exposure limit.

Hand protection

Gloves

Materials	Breakthrough time	Thickness
LDPE (low Density Poly Ethylene)	10 minutes	0.025mm

Eye protection

Protective goggles

Skin and body protection

Head / neck protection.  
Protective clothing

### 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3, and 13

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties.

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosive limits	No data available
Flammability	Extremely flammable aerosol
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	1.1
Vapour pressure	No data available
Solubility	water; insoluble
Relative density	1.1; 20°C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with explosive properties
pH	No data available

**Safety Data Sheet as per regulation (EC) 1907/2006**

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**9.2 Other Information**

Absolute density	1100 kg / m <sup>3</sup> ; 20 °C
------------------	----------------------------------

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

May be ignited by sparks.  
Gas / vapour spreads at floor level: Ignition hazard.

**10.2 Chemical stability**

Stable under normal conditions

**10.3 Possibility of hazardous reactions**

No data available

**10.4 Conditions to avoid**

Conditions to avoid

Use spark / explosion proof appliances and lighting system.  
Keep away from ignition sources / sparks.  
Keep away from naked flames / heat

**10.5 Incompatible materials**

Materials to avoid

No data available

**10.6 Hazardous decomposition products**

Hazardous decomposition products

On burning: release of toxic and corrosive gases / vapours (phosphorous oxides, nitrous vapours, hydrofluoric acid, hydrogen bromide, hydrogen chloride), (carbon monoxide-carbon dioxide).

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**11.1.1 Test results**

**Acute Toxicity**

No (test) data on the mixture available

polymethylene polyphenyl isocyanate						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination
Oral	LD50		>10000 mg/kg		Rat	Literature Study
Dermal	LD50		>5000 mg/kg		Rabbit	Literature Study
Inhalation (vapours)	LD50		10 mg/l-20 mg/l	4h	Rat	Literature Study
Inhalation			category 4			Literature Study

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination
Oral	LD50	EU Method B.1 tris	632 mg/kg bw		Rat (female)	Experimental value
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rat (male/female)	Experimental value
Inhalation (aerosol)	LC50	OECD 403	> 7 mg/l	4 h	Rat (male/female)	Experimental value

triethyl phosphate						
Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination
Oral	LD50		1600 mg/kg		Rat	Inconclusive, insufficient data
Oral	LD50		1370 mg/kg bw		Mouse	Experimental value
Dermal	LD50		> 20000 mg/kg bw		Rabbit	Inconclusive, insufficient data
Inhalation (aerosol)	LC50	OECD 403	> 8.817 mg/l air	4 h	Rat (male/female)	Experimental value

Classification is based on relevant ingredients

**Conclusion**

Harmful if inhaled  
Not classified as toxic in contact with skin  
Not classified as acute toxic if swallowed

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**Corrosion / Irritation**

No (test) data on the mixture available

polymethylene polyphenyl isocyanate						
Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Irritating; Category 2					Literature Study
Skin	Irritating; Category 2					Literature Study
Inhalation	Irritating; STOT SE cat.3					Literature Study

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester						
Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Not irritating	OECD 405	24 h	7 days	Rabbit	Experimental value
Skin	Not irritating	OECD 404	4 h	7 days	Rabbit	Experimental value

triethyl phosphate						
Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination
Eye	Moderately irritating	OECD 405	24 h		Rabbit	Experimental value
Skin	Not irritating	OECD 404	4 h	1; 24; 48; 72; 168 hrs	Rabbit	Experimental value

Classification is based on the relevant ingredients

**Conclusion**

Causes skin Irritation.  
Causes serious eye irritation.  
May cause respiratory irritation  
Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

**Respiratory or skin sensitisation**

No (test) data on the mixture available

polymethylene polyphenyl isocyanate						
Route of exposure	Result	Method	Exposure Time	Observation Time Point	Species	Value determination
Skin	Sensitising; Category 1					Literature Study
Inhalation	Sensitising; Category 1					Literature Study

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester						
Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value

triethyl phosphate						
Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination
Skin	Not sensitizing	OECD 429			Mouse (female)	Experimental value
Inhalation						Data waiving

Classification is based on the relevant ingredients

**Conclusion**

May cause an allergic skin reaction.  
May cause allergic or asthma symptoms or breathing difficulties if inhaled.

**Specific target organ toxicity**

No (test) data on the mixture available

polymethylene polyphenyl isocyanate								
Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation			STOT Re cat.2					Literature Study

**Safety Data Sheet as per regulation (EC) 1907/2006**

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

**reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester**

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	Subchronic toxicity test	171 mg/kg bw/day		No effect	13 weeks (daily)	Rat (female)	Experimental value
Oral (diet)	LOAEL	Subchronic toxicity test	52 mg/kg bw/day	Liver	Weight gain	13 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)	Dose level		0.586 mg/l air		No effect		Mouse (male)	Experimental value

**triethyl phosphate**

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	OECD 407	1000 mg/kg bw/day		No effect	4 weeks (daily)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation (aerosol)	NOAEC	Subchronic toxicity test	366 mg/m3 air		No effect	12 weeks (6h/day, 5 days/week)	Rat (male)	Inconclusive, insufficient data

Classification is based on the relevant ingredients

**Conclusion**

May cause damage to organs through prolonged or repeated exposure if inhaled.

Not classified as sub-chronically toxic in contact with skin

Not classified as sub-chronically toxic if swallowed.

**Mutagenicity (in vitro)**

No (test) data on the mixture available

**reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester**

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 482	Rat liver cells		Experimental value
Negative without metabolic activation, positive with metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value

**triethyl phosphate**

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster lung fibroblasts	No effect	Experimental value
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

**Mutagenicity (in vivo)**

No (test) data on the mixture available

**reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester**

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	OECD 474		Mouse (male/female)	Bone marrow	Experimental value

**triethyl phosphate**

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative			Mouse (male)	Bone marrow	

**Carcinogenicity**

No (test) data on the mixture available

**polymethylene polyphenyl isocyanate**

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Unknown			Category 2					Literature Study

**Safety Data Sheet as per regulation (EC) 1907/2006**

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

**Reproductive toxicity**

No (test) data on the mixture available

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	LOAEL	OECD 416	99 mg/kg bw/day		Rat (female)	Embryotoxicity		Experimental value
Effects on fertility	LOAEL	OECD 416	99 mg/kg bw/day		Rat (male/female)	Weight changes	Female reproductive organ	Experimental value

triethyl phosphate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	OECD 414	625 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
Maternal toxicity	NOAEL	OECD 414	125 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility	NOEL		335 mg/kg bw/day	120 day(s) - 150 day(s)	Rat (male/female)	No effect		Inconclusive, insufficient data

Classification is based on the relevant ingredients

**Conclusion CMR**

Suspected of causing cancer.

Not classified for mutagenic or genotoxic toxicity

Not classified for reprotoxic or developmental toxicity.

**Toxicity other effects**

No (test) data on the mixture available

**Chronic effects from short and long-term exposure**

ON CONTINUOUS / REPEATED EXPOSURE / CONTACT:

Feeling of weakness.  
Itching,  
Skin rash / inflammation.  
May stain the skin  
Dry skin.  
Coughing  
Possible inflammation of the respiratory tract.  
Respiratory difficulties.

**SECTION 12: Ecological information**

**12.1 Toxicity**

No (test) data on the mixture available

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh / Salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96h				Literature study
Toxicity aquatic micro-organisms	EC50	OECD 209	>100 mg/l		Activated sludge			Literature study

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Other	56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	LC50		131 mg/l	48 h	Daphnia magna	Static system	Fresh water	Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	82 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic invertebrates	NOEC	OECD 202	32 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP
Toxicity aquatic micro-organisms	EC50	ISO 8192	784 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value; GLP

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	> 100 mg/l	96 h	Danio rerio		Fresh water	Experimental value; Nominal concentration
Acute toxicity invertebrates	EC50	OECD 202	2705 mg/l	24 h	Daphnia magna		Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50	Other	901 mg/l	72 h	Scenedesmus subspicatus	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic invertebrates	NOEC	Equivalent to OECD 211	31.6 mg/l	21 day(s)	Daphnia magna		Fresh water	Experimental value; Reproduction

Judgement of the mixture is based on test data on the mixture as a whole

**Conclusion**

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No. 1272/2008

**12.2 Persistence and degradability**

polymethylene polyphenyl isocyanate

**Biodegradation water**

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	<60%		Experimental value

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

**Biodegradation water**

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	14 %; GLP	28 day(s)	Experimental value

triethyl phosphate

**Biodegradation water**

Method	Value	Duration	Value determination
OECD 301C: Modified MITI Test (I)	0 %	28 day(s)	Experimental value
OECD 302B: Inherent Biodegradability: Zahn-Wellens/EMPA Test	97 %	28 day(s)	Experimental value

**Conclusion**

Contains non-readily biodegradable component (s)

**12.3 Bioaccumulative potential**

**Log Kow**

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: - fischer FireStop Hand Foam  
 Revision Date: 11.07.2017  
 Version: 3.1.1

Replaces version from 16.05.10  
 Print Date:- 11.07.2017

polymethylene polyphenyl isocyanate

**BCF fishes**

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	Literature study

**Log Kow**

Method	Remark	Value	Temperature	Value determination
	No data available			

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

**BCF fishes**

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	0.8 - 14	6 week(s)	Cyprinus carpio	Experimental value

**Log Kow**

Method	Remark	Value	Temperature	Value determination
EU Method A.8		2.68	30 °C	Experimental value

triethyl phosphate

**BCF fishes**

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	0.5 - 1.3	6 week(s)	Cyprinus carpio	Experimental value

**Log Kow**

Method	Remark	Value	Temperature	Value determination
EU Method A.8		1.11		Experimental value

**Conclusion**

Does not contain bioaccumulative component (s)

**12.4 Mobility in soil**

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

**(log) Koc**

Parameter	Method	Value	Value determination
log Koc	EU Method C.19	2.76	Experimental value

**Volatility (Henry's Law constant H)**

Value	Method	Temperature	Remark	Value determination
0.00042 Pa.m <sup>3</sup> /mol		25 °C		Read-across

**Percent distribution**

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level I	0.01 %	0 %	3.55 %	3.52 %	92.89 %	Read-across

**Conclusion**

Contains component (s) with potential for mobility in the soil

**12.5 Results of PBT and vPvB assessment**

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

**12.6 Other Adverse effects**

**Fluorinated greenhouse gases (Regulation (EU) No 517/2014)**

Contains components included in the list of fluorinated greenhouse gases (Regulation (EU) No. 517/2014)

**Ozone-depleting potential (ODP)**

Not classified as dangerous for the ozone layer (Regulation (EC) No.1005 /02009)

# Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1



Replaces version from 16.05.10

Print Date:- 11.07.2017

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1 Waste treatment methods

#### 13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01 (wastes not otherwise specified in 08: waste isocyanates).

16 05 04 (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Recycle / reuse Remove waste in accordance with local and/or national regulations.

Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste.

Hazardous waste shall be managed responsibly.

All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.

Specific treatment:-Do not discharge into drains or the environment.

#### 13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10 (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

Road (ADR)	Rail (RID)	Inland waterways (ADN)	Sea (IMSBC / IMDG)	Air (ICAO -TI / IATA-DGR)
------------	------------	------------------------	--------------------	---------------------------

### 14.1. UN number

UN number	1950	1950	1950	1950	1950
-----------	------	------	------	------	------

### 14.2. UN proper shipping name

Proper shipping name	Aerosols	Aerosols	Aerosols	Aerosols	Aerosols, flammable
----------------------	----------	----------	----------	----------	---------------------

### 14.3 Transport Hazard class (es)

Hazard Identification number		23			
Class	2	2	2	2.1	2.1
Classification code	5F	5F	5F		

### 14.4. Packing group

Packing group					
Labels	2.1	2.1	2.1	2.1	2.1

### 14.5. Environmental hazards

Marine pollutant				-	
Environmentally hazardous substance mark	no	no	no	no	no

### 14.6. Special precautions for user

Special provisions	190	190	190	63	A145
Special provisions	327	327	327	190	A167
Special provisions	344	344	344	277	A802
Special provisions	625	625	625	327	
Special provisions				344	
Special provisions				959	
Limited quantities	Combination packagings: not more than 1 litre per inner packaging for liquids. A package shall not weigh more than 30kg (gross mass).				30 kg G

# Safety Data Sheet as per regulation (EC) 1907/2006



Commercial Product Name: - fischer FireStop Hand Foam

Revision Date: 11.07.2017

Version: 3.1.1

Replaces version from 16.05.10

Print Date:- 11.07.2017

## 14.7 Transport in bulk according to ANNEX II of Marpol and the IBC Code

Annex II of MARPOL 73/78	Not Applicable
--------------------------	----------------

## SECTION 15: Regulatory Information

### 15.1 Safety, health & environmental regulations / legislation specific for the substance or mixture

#### EU legislation:

Voc content directive 2010/75/EU

VOC content	Remark
18%	
198 g/l	

#### REACH Annex XVII- Restriction

Contains component (s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

#### National legislation Belgium

No data available

#### National legislation: The Netherlands

Waste Identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	9

#### National legislation France

No data available

#### National legislation Germany

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVWS) of 27 July 2005 (Anhang 4)
-----	---

#### polymethylene polyphenyl isocyanate

TRGS905 - Krebserzeugend	3
TRGS905 - Erbgutverändernd	-
TRGS905 - Fruchtbarkeitsgefährdend	-
TRGS905 - Fruchtschädigend	-
TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Sensibilisierende Stoffe	Sa; Atemwegssensibilisierende Stoffe
Hautresorptive Stoffe	H; Hautresorptiv

reaction mass of tris(2-chloropropyl) phosphate and tris(2-chloro-1-methylethyl) phosphate and phosphoric acid, bis(2-chloro-1-methylethyl) 2-chloropropyl ester and phosphoric acid, 2-chloro-1-methylethyl bis(2-chloropropyl) ester

TA-Luft	5.2.5
---------	-------

#### triethyl phosphate

TA-Luft	5.2.5
---------	-------

#### National legislation United Kingdom

No data available

#### Polymethylene polyphenyl isocyanate

Skin Sensitisation	Sen
Respiratory Sensitisation	Sen

#### Other relevant data

No data available

#### Polymethylene polyphenyl isocyanate

IARC - classification	3; Polymethylene polyphenyl isocyanate
-----------------------	--

### 15.2 Chemical Safety Assessment

No chemical safety assessment is required

Safety Data Sheet as per regulation (EC) 1907/2006

Commercial Product Name: - fischer FireStop Hand Foam  
Revision Date: 11.07.2017  
Version: 3.1.1

Replaces version from 16.05.10  
Print Date:- 11.07.2017

**SECTION 16: Other Information**

**Full text of any H-statements referred to under headings 2 and 3:**

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

**CLP (EU-GHS) Classification, Labelling and packaging (Globally Harmonised System in Europe)**

- DMEL Derived Minimal effect Level
- DNEL Derived No effect Level
- EC50 Effect Concentration 50%
- ErC50 EC50 in terms of reduction of growth rate
- LC50 Lethal Concentration 50%
- LD50 Lethal Dose 50%
- NOAEL No Observed Adverse Effect Level
- NOEC No Observed Effect Concentration
- OECD Organisation for Economic Co-operation and Development
- PBT Persistent, Bioaccumulative & Toxic
- PNEC Predicted No Effect Concentration
- STP Sludge Treatment Process
- vPvB very Persistent & very Bioaccumulative

**Specific concentration limits CLP**

polymethylene polyphenyl isocyanate	C ≥ 5 %	Eye Irrit. 2;H319	analogous to Annex VI
	C ≥ 5 %	Skin Irrit. 2;H315	analogous to Annex VI
	C ≥ 0.1 %	Resp Sens 1;H334	analogous to Annex VI
	C ≥ 5 %	STOT SE 3;H335	analogous to Annex VI

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.

