

# Probreathe<sup>®</sup> FR Duo Tape

DOUBLE-SIDED ADHESIVE TAPE FOR FIXING PROBREATHE MEMBRANES

## TECHNICAL CHARACTERISTICS

	Types	Values
Roll size		50mm x 50m
Thickness		220μ
Adhesive mass	Acrylic solvent	
Type of support	Polyester	17μ
Protector	2-sided siliconised kraft	120g
Adhesive strength	Steel	33 N/25mm
According to ARMFA 500 I	ABS	29 N/25mm
Tack (ftm9/pstc I 6)		25 N/25m
Dynamic shear strength after 24 hours		141 N/625mm <sup>2</sup>
Temperature resistance		-30 to 170°C
Elongation at break		10%

The rolls should be stored flat, in their original packaging, protected from dust, light, humidity and solvent fumes, at a temperature between +10°C and +30°C.

Under these conditions, the storage period of the rolls in a temperate climate should not exceed 12 months.

Surfaces must be clean, dry, free of dust, grease, oil or any other contaminant.

The contents of this literature are provided by A. Proctor Group Limited (APG) in good faith and considered to be factual and accurate at the date of publication. These do not constitute specific technical recommendations and are provided for general information purposes only. It is for the engineer, architect or other relevant professional engaged to advise on any project to assess and satisfy themselves on the suitability of APG products for their intended use on that project. Please note that information contained in this literature may be subject to change with advances in usability and experience.



Visit our website...

[www.proctorgroup.com](http://www.proctorgroup.com)



contact@proctorgroup.com | +44 (0) 1250 872261

Issued January 2022